

FOOD GRADE PENETRATING OIL



LUTM104



NSF® Nonfood Compounds Program Listed
H1 Rated (Registration # 145288)

EXTREME
PRESSURE

For use in extreme pressure applications

475 246
°F °C
-40 -40

Minimum - Maximum operational temperature
range: Low -40°F (-40°C) • High 475°F (246°C)

39.0
KV

Dielectric Strength Value: 39,000 volts



Non-Flammable



Features SPRAY ANYWAYTM Nozzle



HMIS Hazard Rating:
Health (1) • Flammability (0) • Reactivity (0)

- Quick penetration
- Non-flammable
- Use to loosen rust, scale & corrosion



PRESERVE. PROTECT. PREVENT.®

Sprayon® LUTM104 Food Grade Penetrating Oil is a synthetic heavy-duty rust penetrant that quickly penetrates nuts and bolts. Its accelerated action loosens rust while penetrating grease, dirt and corrosion. Specifically developed to meet the demands of a safe, low HMIS rating, non-flammable lubricant for food processing areas, LUTM104 Food Grade Penetrating Oil can be used to loosen rust, scale and corrosion around fasteners and hose fittings on food processing equipment.

FOR USE ON

- Rusted or Frozen Lugs
- Bolts • Repair Work
- Food Plant Equipment
- Tight-Fitting Parts
- General Overhaul
- Scales • Fans • Carts
- Galleys • Bottlers • Chutes
- Conveyors • Racks
- Ovens • Stoves • Fillers
- Mixers • Freezers • Rails
- Cooking Appliances

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU104

LUBRICANTS

APPLICATION

Shake well before using. For best results use at room temperature 70°F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

PLASTIC SAFE: Yes (Always test before using)

TEMPERATURE RANGE:

HIGH: 475 °F

LOW: -40 °F

LOAD CAPACITY: Extreme

DIELECTRIC STRENGTH: 39.0 kV

FALEX LOAD (ASTM D-3233A): 3,000 lbs.

DELIVERY: SPRAY ANYWAY™ Nozzle

PACKAGING

STOCK #: S00104000

UPC CODE: 0-75577-00617-5

FILL WT.: 11.75 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: Sprayon.com

CUSTOMER SERVICE:

800-777-2966

TECHNICAL INFORMATION:

800-251-2486

PROPERTIES

APPEARANCE: Clear

BASE: Synthetic

FILM TYPE: Wet

ODOR: Low

CONTAINS P.T.F.E: No

PROPELLANT: CO₂

WT./GAL.: 6.67

SPECIFIC GRAVITY: 0.80

% VOC AEROSOL: 0

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

HEAVY METALS: No

FLAMMABLE: No

FLASH POINT: >200°F

SARA 313: None

PROP 65: None

HAPS: None

HAZARD RATING: 1, 0, 0

SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145288



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.

Scan this code with your mobile phone to download the NSF® Registration Letter for this product



© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966

310-PDS-LU104