FOOD GRADE CHAIN LUBRICANT

LU™205

- NSF H1 — NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145282)
- EXTREME PRESSURE — For use in extreme pressure applications
- 450 °F 232 °C / 12 -11 — Minimum - Maximum operational temperature range: Low 12 ˚F (-11 ˚C) • High 450˚F (232 ˚C)
- BIO OECD 301B — Meets (OECD) 301B Standards - Rapidly Biodegradable after 301B Standard
- HEAVY METALS FREE — Free of heavy metals such as Barium & Cadmium
- CONTAINS P.T.F.E. — Contains P.T.F.E. (polytetrafluoroethylene)
- H 2 / F 4 / R 0 — HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Extreme pressure lubricity
- Foaming action for deep penetration
- Excellent water resistance and anti-wear properties

Sprayon™

PRESERVE. PROTECT. PREVENT.®

Sprayon® LU™205 Food Grade Chain Lubricant is a blend of the finest quality renewable resource oils available, treated with the most effective anti-oxidants, extreme pressure, anti-wear, and corrosion protecting additives. PTFE is added to further enhance load capacity and reduce friction. LU™205 Food Grade Chain Lubricant offers excellent extreme pressure lubricity, water resistance and high temperature performance on chains and much more. Foaming action allows for pin-point application and deep penetration.

LUBRICANTS

FOR USE ON
- Fans • Bearings • Pumps
- Conveyors • Cables
- Electrical Motors • Locks
- Air Tools • Hinges
- Conveyor Chains
- Packaging Equipment
- Hoist Chains
- Link & Roller Assemblies

FOR USE BY
- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors

LU205

APPLICATION
Shake Well Before using. For best results use at room temperature 70˚F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE
PLASTIC & RUBBER SAFE: Yes (Always test before using)
TEMPERATURE RANGE:
HIGH: 450 ˚F
LOW: 12 ˚F
LOAD CAPACITY: Extreme
DIELECTRIC STRENGTH: 46.5 kV
FALEX LOAD (ASTM D-3233A): 3,750 lbs.
4-BALL WEAR SCAR (ASTM D-2266): 0.44 mm
RAPIDLY BIODEGRADABLE (OECD-301): Yes
DELIVERY: SPRAY ANYWAY™ Nozzle

PROPERTIES
APPEARANCE: Light Straw Color
BASE: Bio-based (Vegetable)
FILM TYPE: Wet
ODOR: Low
CONTAINS P.T.F.E: Yes
PROPELLANT: Hydrocarbon Blend
WT./GAL.: 6.86
SPECIFIC GRAVITY: 0.83
% VOC AEROSOL: 15
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
HEAVY METALS: No
FLAMMABLE: Yes
FLASH POINT: <0°F
SARA 313: None
PROP 65: None
HAPS: None
HAZARD RATING: 2, 4, 0
SHELF LIFE: 3 years from date of manufacture

PACKAGING
STOCK #: S00205000
UPC CODE: 0-75577-00618-2
FILL WT.: 15 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING
Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES
MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE:
800-777-2966
TECHNICAL INFORMATION:
800-251-2486

NSF® NONFOOD COMPOUNDS PROGRAM LISTED
H1 Rated - Registration #145282

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.

Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.®

Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966