

# ALL-PURPOSE SILICONE LUBRICANT



## LU™ 206



Light Pressure Lubricant



Minimum - Maximum operational temperature range: Low -50°F (-46°C) High 550°F (288°C)



5% Silicone



Features Spray Anyway™ nozzle



HMIS Hazard Rating:  
Health (2) • Flammability (4) • Reactivity (0)

- Works from -50°F to 550°F
- Does not interfere with painting operations
- Compatible with most surfaces




PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 206 All-Purpose Silicone Lubricant is an economical lubricant for applications where petroleum based products are not desired. This 5% silicone formula protects against air and moisture to retard oxidation and corrosion. It virtually eliminates friction and sticking to improve high-speed production. Leaves a long-lasting film that is compatible with most surfaces. Equipped with an extension tube for hard-to-reach areas.

## USES

- Windows
- Rubber components
- Doors
- Plastic assemblies
- Drawers
- Dissimilar metals
- Hinges
- Sliding wood surfaces
- Springs
- Layout tables
- Leather
- Weatherstripping



LU206

## LUBRICANTS

### APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 14" from surface.

### PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -50°F

HIGH: 550°F

LOAD CAPACITY: Light

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Eliminates sticking
- Improves high speed production
- Retards oxidation and corrosion

### PHYSICAL

APPEARANCE: Clear liquid

ODOR: Slight solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.43

SPECIFIC GRAVITY: 0.65

VISCOSITY: Medium

PAINTABLE: Yes

% VOC AEROSOL: 94.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

### PACKAGING

Stock #: S00206

UPC Code: 0-75577-90206-4

Fill Wt.: 10 oz.

Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

### RESOURCES

MSDS/EDS/PRODUCT

DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

### SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

**USA Roller Chain & Sprockets**  
**sales@usarollerchain.com**  
**(407) 347-3519**

PRESERVE. PROTECT. PREVENT.



**Sprayon® Products**

101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
1-800-777-2966

310-PDS-LU206