

ECO-GRADE™ GENERAL PURPOSE LUBRICANT & PENETRANT



LU™ 402



For use in light pressure applications



Minimum - Maximum operational temperature range: Low -5 °F (-15 °C) • High 370 °F (188 °C)



Features Spray Anyway® Nozzle



Free of Heavy Metals such as Barium & Cadmium



Conforms to manufacturers Green Cert™ Specifications



HMS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- Rapidly Biodegradable
- Formulated with Rapeseed Oil
- Prevents Rust
- Quick Penetration



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 402 Eco-Grade™ General Purpose Lubricant & Penetrant is a biodegradable 3 & 1 penetrant and lube that quickly penetrates and dissolves rust, gum and corrosion. Loosens stuck parts, lubricates and prevents rust and corrosion. It is formulated with renewable resource ingredients, which are friendly to workers and the environment.



LUBRICANTS

USES

- Release of rusted or frozen lugs and bolts
- Lubrication of tight-fitting parts
- General overhaul
- Repair work
- Food plant equipment

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70°F). Shake well before using. Spray at a distance of 10" to 12" from surface.

CERTIFICATIONS



PROPERTIES

APPEARANCE: Light translucent yellow
ODOR: Sweet
PROPELLANT: Hydrocarbon
WT./GAL.: 6.83
SPECIFIC GRAVITY: 0.82
VISCOSITY: Water-like
PAINTABLE: No
SARA 313 Chemicals: No
PROP 65 Chemicals: No
% VOC AEROSOL: 15%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: <0°F
HAZARD RATING: 2,3,0
SHELF LIFE: 3 years from date of manufacture

PERFORMANCE

TEMPERATURE RANGE:
LOW: 5°F
HIGH: 370°F
LOAD CAPACITY: Low

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Equipped with SPRAY ANYWAY™ valve
- Equipped with an extension tube for hard-to-reach areas

PACKAGING

STOCK #: S00402000
UPC CODE: 0-75577-84925-3
FILL WT.: 12 oz.
PER CASE: 12
CARTON DIMENSIONS:
 L 11.13" x W 8.44" x H 8.38"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:
sprayon.com
CUSTOMER SERVICE:
 1-800-777-2966
TECHNICAL INFORMATION:
 1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

*Green Cert's mission: To reduce environmental impact and to meet or exceed the most stringent regulatory requirements without sacrificing product quality. To learn more, please visit GreenCert.com

**Any product that does not contain greenhouse gases will have the greenhouse gas free logo on the label. For a complete listing of all our greenhouse gas free products, visit our website or contact our customer service department at 800-777-2966.

***Readily biodegradable as determined by the Carbon Dioxide Evolution Test Method (OECD Guideline 301B) by Wildlife International, Ltd



LU402



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
 101 Prospect Ave. NW
 Cleveland, OH 44115
Sprayon.com
 1-800-777-2966

310-PDS-LU402