

FOOD GRADE MACHINERY OIL



LUTM701



NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145297)



For use in light pressure applications



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 500 °F (260 °C)



Flash Point: 200 °F (93 °C)



Dielectric Strength Value: 27,500 volts



Wide delivery spray covers a wide surface area in a short amount of time



HMS Hazard Rating: Health (2) • Flammability (0) • Reactivity (0)

- Meets FDA requirements
- Resists corrosion and chemical attack
- High purity white mineral oil for general purpose applications
- Wide delivery spray covers a wide surface area in a short amount of time



PRESERVE. PROTECT. PREVENT.®

Sprayon® LUTM701 Food Grade Machinery Oil is recommended to lubricate food and beverage processing equipment. This high purity white mineral oil penetrates and loosens rust, dirt, scale and corrosion. Provides effective lubrication to free up rusted or corroded parts. Will not harm paint, plastic or wood surfaces. Meets FDA regulations 172.878, 178.3620 and 573.680. Does not contain silicone.

LUBRICANTS

FOR USE ON

- Bottle & Carton Filling Machinery
- Valves • Pistons • Rollers
- Stainless Steel Pumps
- Chain Drive Belts
- Paste & Sauce Fillers
- Cams on Rotary-Type Fillers
- Mixers • Conveyors

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU701

APPLICATION

Shake well before using. Do not apply while equipment is running. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to set. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

- PLASTIC SAFE:** Yes
TEMPERATURE RANGE:
HIGH: 500 °F
LOW: -20 °F
LOAD CAPACITY: Light
- Penetrant
 - Rust Inhibitor
 - Does not contain silicone.
 - Will not harm paint, plastic, or wood surfaces.
 - Non-gumming fluid at low temperatures.
 - Virtually odorless, tasteless and colorless.

PACKAGING

STOCK #: S00701000
UPC CODE: 0-75577-00626-7
FILL WT.: 12.75 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE:
800-777-2966
TECHNICAL INFORMATION:
800-251-2486

PROPERTIES

APPEARANCE: Clear
BASE: Mineral Oil
FILM TYPE: Wet
ODOR: Low Odor
PROPELLANT: CO₂
WT./GAL.: 6.70
SPECIFIC GRAVITY: 0.81
PAINTABLE: No
H.A.P.S. (Hazardous Air Pollutants): No
SARA 313 Chemicals: No
PROP 65: No
% VOC AEROSOL: 67.5
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: No
FLASH POINT: >200 °F
HAZARD RATING: 2, 0, 0
SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145297



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2011 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966

310-PDS-LU701