





HIGH PERFORMANCE DRY LUBRICANT



LU™ 708

- 
For use in extreme pressure applications
- 
Contains P.T.F.E. (polytetrafluoroethylene)
- 
Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 572 °F (300 °C)
- 
HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Works from -40°F to +572°F
- Safe on most plastics
- Lowest coefficient of friction
- Formulated with P.T.F.E.



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 708 High Performance Dry Lubricant is a clean, non-oily, non-staining, versatile dry lubricant that functions from -40°F to +572°F. It is a chemically inert formula that dries quickly to a white film to show coverage. This product does not contain silicone or chlorinated solvents. The extremely low static coefficient of friction makes it a superb lubricant where low speeds and light loads are involved. LU™ 708 High Performance Dry Lubricant has great anti-stick properties for use as an effective release agent.

LUBRICANTS

USES

- Metal extrusions
- Elastomers
- Locks and catches
- Spray booths
- Drawers & hinges
- Window guides
- Machine parts
- Conveyor belts
- Chutes and slides
- Tanks
- Industrial blenders
- Bins

Use as a Release Agent on: Synthetic fibers, cord, twine or rope & most plastics.

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 572°F

LOAD CAPACITY: Light pressure

- Penetrant
- Water-Displacer
- Rust Inhibitor

PROPERTIES

APPEARANCE: Translucent white film

ODOR: Mild Solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.31

SPECIFIC GRAVITY: 0.64

PAINTABLE: No

% VOC AEROSOL: 98.41%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00708

UPC Code: 0-75577-90708-3

Fill Wt.: 10 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



LU708



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
 Cleveland, OH 44115
 Sprayon.com
 1-800-777-2966

310-PDS-LU708