

HIGH PERFORMANCE WET LUBRICANT



LU™ 727



For use in extreme pressure applications

CONTAINS P.T.F.E.

Contains P.T.F.E. (polytetrafluoroethylene)



Minimum - Maximum operational temperature range: Low -40 °F (-18 °C) • High 450 °F (232 °C)

FLASH POINT °F/°C 200/93

Flash Point: 200 °F (93 °C)



HMS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Exceeds Fed 791 water displacement
- Works from -40°F to +450°F
- Dielectric strength: 47,000 volts
- High flash
- Formulated with P.T.F.E.



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 727 High Performance Wet Lubricant penetrates deep into corroded areas to clean and dissolve rust, grease and dirt, even in the tightest tolerances. This top performer displaces moisture, lubricates and provides a protective film to guard against humidity and corrosion over a wide temperature range. Because of its wide operating temperature and high dielectric strength, LU™ 727 High Performance Wet Lubricant is an excellent choice for electrical applications. It will ensure maximum protection against extreme pressure, friction and wear on all moving parts.

USES

- Hinges
- Bearings
- Cables
- Springs
- Wheel hubs
- Chains
- Nuts
- Sprockets
- Bolts
- Locks
- Sliding surfaces
- Tools
- Rollers
- Guide bars
- Pulleys
- Electric motors



LU727

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

DIELECTRIC STRENGTH: 47,000 volts

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 450°F

LOAD CAPACITY: Extreme pressure

ASTM D-2625A: 4,500 lbs. pressure

4-BALL WEAR TEST (ASTM D-2266):

No break-down at a distance of 76 mm

HUMIDITY CABINET TEST (ASTM D-1748):

900 hrs. @ 120°F - pass

- Penetrant

- Water-Displacer

- Rust Inhibitor

PROPERTIES

APPEARANCE: Transparent amber

ODOR: Petroleum

PROPELLANT: CO₂

PAINTABLE: No

WT./GAL.: 6.73

SPECIFIC GRAVITY: 0.81

H.A.P.S. (Hazardous Air Pollutants): No

SARA 313 Chemicals: No

PROP 65: No

% VOC AEROSOL: 0.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: No

FLASH POINT: >200°F

HAZARD RATING: - 2,4,0;

SHELF LIFE: 3 years from date of manufacture

PACKAGING

Stock #: S00727

UPC Code: 0-75577-90727-4

Fill Wt.: 9.25 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

1-800-777-2966

310-PDS-LU727