








INDOOR METAL PROTECTANT



LU™ 767

- 
For use in light pressure applications
- 
Protectant Longevity: Medium 12-15 months
- 
NSF® Registered; H2 Rated (Lubricants with no contact) (Reg. No. 127541)
- 
Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 302 °F (150 °C)
- 
Flash Point: 188 °F (87 °C)
- 
Dielectric strength value: 48,200 Volts
- 
HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Penetrates/displaces moisture/prevents rust
- 15 Month durability
- Meets MIL-C-23411
- Lubricant & corrosion inhibitor



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 767 Indoor Metal Protectant is a medium weight oil formulated for excellent lubrication. This product has ideal corrosion protection, moisture displacement, and penetration properties. The protective film is non-staining and works up to 15 months against humidity and corrosion damage and is non-conductive. LU™ 767 Indoor Metal Protectant is ideal for storage of items indoors and items to be shipped. This product leaves an amber film showing total coverage of the object sprayed. This product is safe on metals, rubber, plastic and painted surfaces.

USES

- Industrial parts & machines
- Valves
- Castings
- Oil field equipment
- Locks
- Sheet steel
- Assemblies
- Electrical equipment
- Dies
- Automotive parts
- Machine tools
- Aircraft parts
- Bearings
- Military equipment
- Molds & Tools
- Ignitions
- Threads, Gears & Hinges
- Weapons
- Railroad equipment
- Electronic communications equipment



LU767

© 2010 Sprayon® Products Made in U.S.A.

Distributed by:
USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

DIELECTRIC STRENGTH: 48,200 volts

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -20°F

HIGH: 302°F

LOAD CAPACITY: Light

GOVERNMENT SPECIFICATIONS:

This product meets the requirements of MIL-C-16173D Grade 3, MIL-C-23411A and MIL-C-81309D Type III.

- NSF Reg. No. 127541; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor

PROPERTIES

APPEARANCE: Light Amber

ODOR: Mild Solvent

PROPELLANT: CO₂

WT./GAL.: 6.71

SPECIFIC GRAVITY: 0.81

PAINTABLE: No

H.A.P.S. (Hazardous Air Pollutants): No

PROP 65: No

% VOC: 25.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: 188°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00767

UPC Code: 0-75577-90767-0

Fill Wt.: 11 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

