

FOOD GRADE SILICONE LUBRICANT




LU™ 910



For use in light pressure applications



3.5% Silicone



Minimum - Maximum operational temperature range: Low -58 °F (-50 °C) • High 575 °F (302 °C)



Features Spray Anyway® Nozzle



HMIS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- Formulated Without Methylene Chloride
- Works from -58°F to +575°F
- Meets FDA Regulations
- Low Viscosity - No Buildup



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 910 Food Grade Silicone Lubricant is a low viscosity silicone that is colorless, odorless and tasteless. Sprayon's formula is effective from -58°F (-50°C) to 575°F (302°C). Prevents "sticking" without transferring to end products. LU™ 910 Food Grade Silicone Lubricant can be used in proximity to foods where petroleum products and other organics would contaminate. Meets FDA regulations when no more than 1 PPM residual is imparted.

USES

- Slides
- Guide rails
- Knives
- Slicers
- Saws
- Grinders
- Dough mixers
- Guards
- Heat sealing equipment
- Conveyors
- Food racks
- Ovens
- Bottling machines
- All food and drug processing



LU910

© 2010 Sprayon® Products Made in U.S.A.

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

NOTE: May harm certain plastics (styrene or urethane types), elastomers and air-dried painted surfaces. Test product on non-essential similar material prior to application.

PERFORMANCE

PLASTIC SAFE: No

TEMPERATURE RANGE:

LOW: -58°F

HIGH: 575°F

LOAD CAPACITY: Light

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Meets FDA regulations when no more than 1 ppm is applied
- Equipped with SPRAY ANYWAY™ valve
- Equipped with an extension tube for hard-to-reach areas

PACKAGING

Stock #: S00910000

UPC Code: 0-75577-75931-6

Fill Wt.: 12 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PHYSICAL

APPEARANCE: Clear liquid

ODOR: Chlorinated

PROPELLANT: Hydrocarbon

WT./GAL.: 6.4

SPECIFIC GRAVITY: 0.77

VISCOSITY: Low

PAINTABLE: No

% VOC AEROSOL: 50.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,3,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486



Distributed by:

USA Roller Chain & Sprockets
sales@usarollerchain.com
(407) 347-3519



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

1-800-777-2966

310-PDS-LU910