# **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

Date of Preparation Jun 15, 2018

04 00 [1047]

	DUCT NUMBER						
S20605000							
PRO	DUCT NAME						
LL	J206L All-Purpose Silicone	e Lubricant					
	UFACTURER'S NAME						
	PRAYON PRODUCTS						
	PRAYON PRODUCTS GR	ROUP					
	01 W. Prospect Avenue,						
С	leveland, OH 44115						
	is document includes all data re						
All	data given below are MAXIMUI			the product AS (	CURRENTLY FO	RMULATED. Var	iations may occur
	on individual batches due to ac	ljustments made during p	roduction.				
Produ	ict Weight	Specific Gr	avity		FLASH		
	95 lb/gal	0.72	avity			°F PMCC	
	d Category (for SARA 311.312				10	1 1 1100	
	cute   Chronic   Fire	-)					
	le Ingredients						
	nical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
	phatic Hydrocarbon Solvent	N		N			
64	742-89-8	N	Ν	IN	Ν	5	5
Light	Aliphatic Hydrocarbon Solvent	N	N	N	N	84	86
	742-49-0	N	Ν	IN	IN	84	80
Methy	/l Cyclohexane	N	N	N	N	5	4
10	8-87-2	IN	IN	IN	IN	5	4
-				-			
Vc	platile Organic Compou	Inds ILS FPA					
VC							
•	Conting Danaity	E OE lb/acl	710 ~/				
A.	Coating Density Total Volatiles	5.95 lb/gal 93.0% by wt.	712 g/l 94.7% b	v vol			
В. С.	Federally exempt solvents:	93.0% by wi.	94.7% D	y voi.			
С.	Water	0.0% by wt.	0.0% b	v vol			
D.	Organic Volatiles	93.0% by wt.	94.7% b				
Б. Е.	Percent Non-Volatile	7.0% by wt.	5.3% b				
F.	VOC Content	5.52 lb/gal	662 g/l	total			
••	Voo ooment	5.52 lb/gal	662 g/l		exempt solvents		
			> 11983 g/l	of sol			
		13.27 lb/lb	13.27 kg/kg of solids				
	93.0% by wt LVP-VOC						
	Maximum Incre	mental Reactivity (MIR)	(per US EPA	Aerosol Ctq R	ule, MIR Values	2009)	
1.03							
Vo	platile Organic Compou	unds - California					
Α.	Coating Density	5.95 lb/gal	712 g/	ı			
А. В.	Total Volatiles	93.0% by wt.	/ 12 y/	i % by vol.			
		93.0% by wi.	94.77	% by voi.			
C.	Exempt solvents: Water	0.0% by wet	0.00	/ huvol			
D.		0.0% by wt. 93.0% by wt.		% by vol.			
D. E.	Organic Volatiles Percent Non-Volatile	2		% by vol.			
E. F.	VOC Content	7.0% by wt.		% by vol.	total		
г.	voc content	5.52 lb/gal	662 g/		total	onto	
		5.52 lb/gal	662 g/		less exempt solve	51115	
		> 99.99 lb/gal	> 11983 g/		of solids		
		13.27 lb/lb	13.27	′ kg/kg	of solids		

93.0% by wt LVP-VOC Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.03

## Volatile Organic Compounds - South Coast Air Quality Management District, California, US

А. В. С.	Coating Density Total Volatiles Exempt solvents:	5.95 lb/gal 93.0% by wt.	712 g/l 94.7% by vol.	
	Water	0.0% by wt.	0.0% by vol.	
D.	Organic Volatiles	93.0% by wt.	94.7% by vol.	
E.	Percent Non-Volatile	7.0% by wt.	5.3% by vol.	
F.	VOC Content	5.52 lb/gal	662 g/l	total
		5.52 lb/gal	662 g/l	less exempt solvents
		> 99.99 lb/gal	> 11983 g/l	of solids
		13.27 lb/lb	13.27 kg/kg	of solids
		93.0%		by wt LVP-VOC

## Volatile Organic Compounds - EU Directive 2010/75/EU

Total Volatiles	93.0% by wt.	94.7% by vol
VOC Content	5.52 lb/gal	662 g/l

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

Volatile HAPS	0.00	lb/gal	0.000	kg/l
	0.00	lb/gal	0.000	kg/l of solids
	0.00	lb/lb	0.00	kg/kg of solids

#### **Air Quality Data**

Density of Organic Solvent Blend 5.84 lb/gal Photochemically Reactive Yes

## Additional Regulatory Information

US EPA TSCA: Not Applicable Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

## Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.