SAFETY DATA SHEET

SC0208LQ0

| Section 1. Identification | | |
|--|--|--|
| Product name | : LU™208 LQ Cutting Oil | |
| Product code | : SC0208LQ0 | |
| Other means of identification | : Not available. | |
| Product type | : Liquid. | |
| Relevant identified uses of | the substance or mixture and uses advised against | |
| Paint or paint related materia | l. | |
| Manufacturer | : Sprayon Products Group 101 W. Prospect Avenue, Cleveland, Ohio 44115 | |
| Emergency telephone number of the company | : US / Canada: (800) 424-9300 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year | |
| Product Information Telephone Number | : US / Canada: (800) 247-3266 Mexico: Not Available | |
| Regulatory Information Telephone Number | : US / Canada: (216) 566-2902 Mexico: Not Available | |
| Transportation Emergency Telephone Number | : US / Canada: (800) 424-9300 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year | |

Section 2. Hazards identification

LU™208 LQ Cutting Oil

SC0208LQ0

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). | | |
|--|---|--|--|
| Classification of the substance or mixture | : ASPIRATION HAZARD - Category 1 | | |
| GHS label elements Hazard pictograms | | | |
| Signal word Hazard statements | : Danger : May be fatal if swallowed and enters airways. | | |
| Precautionary statements | | | |
| Prevention | : Not applicable. | | |
| Response | IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. | | |
| Storage | : Store locked up. | | |
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. | | |
| Date of issue/Date of revision | : 12/10/2019 Date of previous issue : 10/30/2018 Version : 9 1/11 | | |

SHW-85-NA-GHS-US

Section 2. Hazards identification

| Supplemental label elements | FOR INDUSTRIAL USE ONLY. |
|-----------------------------|--|
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |

Hazards not otherwise classified

Section 3. Composition/information on ingredients

: None known.

| Substance/mixture | : Mixture |
|-------------------------------|------------------|
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|-----------------|------------------------|--------------------------|
| | ≥25 - ≤50 ≥25 - ≤50 | 64742-52-5 64742-65-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. | | |
|--------------|--|--|--|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | | |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. | | |
| Ingestion | : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. | | |

Most important symptoms/effects, acute and delayed Potential acute health effects

 Date of issue/Date of revision
 : 12/10/2019
 Date of previous issue
 : 10/30/2018
 Version
 : 9
 2/11

 SC0208LQ0
 LU™208 LQ Cutting Oil
 SHW-85-NA-GHS-US
 SHW-85-NA-GHS-US

Section 4. First aid measures

| Eye contact | : No known significant effects or critical hazards. | |
|----------------------------|---|--|
| Inhalation | : No known significant effects or critical hazards. | |
| Skin contact | : No known significant effects or critical hazards. | |
| Ingestion | : May be fatal if swallowed and enters airways. | |
| Over-exposure signs/sym | <u>otoms</u> | |
| Eye contact | : No specific data. | |
| Inhalation | : No specific data. | |
| Skin contact | : No specific data. | |
| Ingestion | : Adverse symptoms may include the following: nausea or vomiting | |
| Indication of immediate me | dical attention and special treatment needed, if necessary | |
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | |
| Specific treatments | : No specific treatment. | |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. It ma be dangerous to the person providing aid to give mouth-to-mouth resuscitation. | |
| | | |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbonyl halides |
| Special protective actions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protective equipment and emergency procedures | | | |
|---|--|--|--|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. | | |
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | | |

| Date of issue | e/Date of revision | : 12/10/2019 | Date of previous issue | : 10/30/2018 | Version : 9 | 3/11 |
|---------------|--------------------|--------------|------------------------|--------------|------------------|------|
| SC0208LQ0 | LU™208 LQ Cutting | g Oil | | | SHW-85-NA-GHS-US | |

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | CAS # | Exposure limits | |
|--|------------|--|------|
| Heavy Naphthenic Petroleum Oil | 64742-52-5 | OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2019). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist | |
| Heavy Paraffinic Oil | 64742-65-0 | OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2019). | |
| Date of issue/Date of revision : 12/10/2019 Date of previous is SC0208LQ0 LU™208 LQ Cutting Oil | | : 10/30/2018 Version : 9 SHW-85-NA-GHS-US | 4/11 |

Section 8. Exposure controls/personal protection

| frac NIC T | TWA: 5 mg/m ³ 8 hours. Form: Inhalable action IOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist |
|------------------|--|
|------------------|--|

Occupational exposure limits (Canada)

| Ingredient name | CAS # | Exposure limits |
|----------------------|------------|--|
| Heavy Paraffinic Oil | 64742-65-0 | CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist 15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m ³ 8 hours. Form: mist STEV: 10 mg/m ³ 15 minutes. Form: mist |

Occupational exposure limits (Mexico)

| | CAS # | Exposure limits | |
|----------------------|------------|---|---------|
| Heavy Paraffinic Oil | 64742-65-0 | NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 5 mg/m³ 8 hours. Form: mist | |

| Appropriate engineering | Good general ventilation should be sufficient to control worker exposure to airborne | |
|---------------------------------|--|----|
| controls | contaminants. | |
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure hey comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment vill be necessary to reduce emissions to acceptable levels. | |
| Individual protection measur | | |
| Hygiene measures | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safet showers are close to the workstation location. | у |
| Eye/face protection | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless he assessment indicates a higher degree of protection: safety glasses with side-shields. | |
| Skin protection | | |
| Hand protection | Chemical-resistant, impervious gloves complying with an approved standard should b worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. | is |
| Body protection | Personal protective equipment for the body should be selected based on the task bein performed and the risks involved and should be approved by a specialist before nandling this product. | ng |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by specialist before handling this product. | |

| Date of issue/Date | of revision | : 12/10/2019 | Date of previous issue | :10/30/2018 | Version : 9 | 5/11 |
|--------------------|----------------------|--------------|------------------------|-------------|------------------|------|
| SC0208LQ0 | LU™208 LQ Cutting Oi | il | | | SHW-85-NA-GHS-US | |

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

| <u>Appearance</u> | |
|--|---|
| Physical state | : Liquid. |
| Color | : Not available. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| рН | : Not available. |
| Melting point/freezing point | : Not available. |
| Boiling point/boiling range | : Not available. |
| Flash point | : Closed cup: >94°C (>201.2°F) |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Not available. |
| Vapor pressure | : Not relevant/applicable due to nature of the product. |
| Vapor density | : Not available. |
| Relative density | : 0.88 |
| Solubility | : Not available. |
| Partition coefficient: n- octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |
| Molecular weight | : Not applicable. |
| Aerosol product | |
| Heat of combustion | : 29.12 kJ/g |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

| Date of issue/Date | of revision | : 12/10/2019 | Date of previous issue | : 10/30/2018 | Version :9 | 6/11 |
|--------------------|---------------------|--------------|------------------------|--------------|--------------|-------|
| SC0208LQ0 | LU™208 LQ Cutting O | il | | | SHW-85-NA-GH | IS-US |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-----------------------------------|--------------------------|---------------|----------------------------|----------|
| Heavy Naphthenic Petroleum Oil | LD50 Oral | Rat | >5000 mg/kg | - |
| Heavy Paraffinic Oil | LD50 Dermal LD50 Oral | Rabbit Rat | >5000 mg/kg >5000 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-----------------------------------|------------------------|---------|-------|----------|-------------|
| Heavy Naphthenic Petroleum Oil | Skin - Severe irritant | Rabbit | - | 500 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Name | Result |
|----------------------|--------------------------------|
| Heavy Paraffinic Oil | ASPIRATION HAZARD - Category 1 |

| Information on the likely routes of exposure | : Not available. | | |
|--|--|---------------------------------|------|
| Potential acute health effe | <u>ects</u> | | |
| Eye contact | : No known significant effects or critical hazards. | | |
| Inhalation | : No known significant effects or critical hazards. | | |
| Skin contact | : No known significant effects or critical hazards. | | |
| Ingestion | : May be fatal if swallowed and enters airways. | | |
| Symptoms related to the Eye contact Inhalation | physical, chemical and toxicological characteristics No specific data. No specific data. | | |
| Skin contact | No specific data. | | |
| Ingestion | : Adverse symptoms may include the following: nausea or vomiting | | |
| Date of issue/Date of revisionSC0208LQ0LU™208 LQ C | : 12/10/2019 Date of previous issue : 10/30/2018 utting Oil | Version : 9 SHW-85-NA-GHS-US | 7/11 |

Section 11. Toxicological information

| Delayed and immediate effects and also chronic effects from short and long term exposure | | | |
|--|---|--|--|
| <u>Short term exposure</u> | | | |
| Potential immediate effects | : Not available. | | |
| Potential delayed effects | : Not available. | | |
| Long term exposure | | | |
| Potential immediate effects | : Not available. | | |
| Potential delayed effects | : Not available. | | |
| Potential chronic health effects | | | |
| Not available. | | | |
| General | : No known significant effects or critical hazards. | | |
| Carcinogenicity | : No known significant effects or critical hazards. | | |
| Mutagenicity | : No known significant effects or critical hazards. | | |
| Teratogenicity | : No known significant effects or critical hazards. | | |
| Developmental effects | : No known significant effects or critical hazards. | | |
| Fertility effects | : No known significant effects or critical hazards. | | |
| Numerical measures of tox | icity | | |

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|-------------------------------|-----------------------|-----------------------|--------------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | - | - | - | - | - |

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

| Proper shipping name | : Not available. |
|----------------------|------------------|
| Ship type | : Not available. |
| Pollution category | : Not available. |

Section 15. Regulatory information

<u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

| Not applicable. | |
|---------------------------|---|
| International regulations | |
| International lists | Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined. Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| | Classification | Justification |
|--------------------------------|--|--|
| ASPIRATION HAZARD - C | ategory 1 | Calculation method |
| History | | |
| Date of printing | : 12/10/2019 | |
| Date of issue/Date of revision | : 12/10/2019 | |
| Date of previous issue | : 10/30/2018 | |
| Version | : 9 | |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification at IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffi MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available | cient of Pollution From Ships, 1973 |
| Date of issue/Date of revision | : 12/10/2019 Date of previous issue : 10/30/2018 | Version : 9 10/11 |
| C0208LQ0 LU™208 LQ C | itting Oil | SHW-85-NA-GHS-US |

Section 16. Other information

SGG = Segregation Group UN = United Nations

V Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.