



**1051 CHEYENNE AVE.  
GRAFTON, WI 53024  
PH. 262-377-8810**

**CATALOG #:****CONN. DIAGRAM:** A-102005-109LE**OUTLINE:** B-104191LE-631**WINDING #:** ZC280 R1 3**MOUNTING:** F1 ONLY**TYPICAL MOTOR PERFORMANCE DATA**

HP	kW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
1/2	0.37	3600	3450	56C	EPFC	N	N

PH	Hz	VOLTS	AMPS	START TYPE	DUTY	INSL	S.F.	AMB°C
1	60	115/208-230	8.4/4-4.2	ACROSS THE LINE	CONTINUOUS	B3	1.0	40

<b>FULL LOAD EFF:</b> 59.5	<b>3/4 LOAD EFF:</b> 54	<b>1/2 LOAD EFF:</b> 45	<b>GTD. EFF</b>	<b>ELEC. TYPE</b>
<b>FULL LOAD PF:</b> 70	<b>3/4 LOAD PF:</b> 63	<b>1/2 LOAD PF:</b> 54.5	55	CAP START IND RUN

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C
12 OZ-FT	49.6 / 24.8	46 OZ-FT 383 %	37.5 OZ-FT 312 %	50

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS / HOUR	APPROX. MOTOR WGT
- dBA	- dBA	0 LB-FT^2	- LB-FT^2	- SEC.		28 LBS.

**\*\*\* SUPPLEMENTAL INFORMATION \*\*\***

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
C-FACE	STANDARD	RIGID	HORIZONTAL	FALSE	EXP PROOF CL I GR C&D CL II GR F&G T3C	FALSE	NONE	BLUE - LEESON (ENAMEL)

BEARINGS	GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	ODE					
BALL	BALL	POLYREX EM	STANDARD 56	NONE	NONE	1144 STRESSPROOF (C-223)
6203	6203					ROLLED STEEL

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	AUTOMATIC	NONE	NONE	NONE	FALSE	NONE VOLTS

\*

**INVERTER TORQUE:** NONE**INV. HP SPEED RANGE:** NONE

N

**ENCODER:** NONE

NONE NONE

O

NONE NONE PPR

T

**BRAKE:** NONE NONE

E

NONE P/N NONE

NONE NONE

S

NONE FT-LB NONE V NONE Hz

\*